

Lovibond® Colour Measurement Tintometer® Group



TR 520 Spectrophotometer



- Compact, Lightweight and Easy to use Sphere Spectrophotometer
- Designed for Fast, Accurate and Precise Colour Measurement
- On Screen Target Display Allows Positioning to be Perfect Every Time
- OnShade Software Included for FREE – Perfect for Detailed Data Analysis

Ürün No: 403035

Handheld and Portable

Weighing only 600 grams, the TR 520 is the perfect lightweight portable spectrophotometer. It's compact and ergonomic design offers easy one-handed operation, helping to prevent operator fatigue and enabling more measurements per hour. Offering the possibility of 5000 measurements with 8 hours battery life enables the TR 520 to be used anywhere on site for a prolonged period of time.

Accuracy

Giving accurate and repeatable results is what the TR 520 does best. The on board camera based locator, enables the user to position the instrument accurately on the chosen sample with minimal contact. This feature dramatically minimize the chances of geometric metamorphism.

Aperture Options

Choosing the correct aperture size for your surface is extremely important for accurate measurement. The TR 520 gives you the flexibility to adjust aperture size from 10mm/8mm to 5mm/4mm with the switch of a button. This adjustability of aperture helps to ensure the instrument is perfect for your measurement needs.

Calibration

The calibration board supplied with every TR 520 incorporates a white tile and black calibration plate. This allows minimum and maximum readings to be checked every 24 hours.

FREE Software

As standard, the TR 520 comes with a FREE PC software package. The OnShade software allows for a detailed data analysis which can then be shared or printed via the optional micro printer accessory.

Suitable for Multiple Applications

The versatility of the TR 520 means its suitable for multiple applications and has the ability to report CIE Lab, XYZ, Yxy, LCh, CIE LUV, Hunter Lab colour spaces, $\Delta E^*L^*a^*b^*$, $\Delta E^*C^*h^\circ$, ΔE^*uv , ΔE^*94 , $\Delta E^*cmc(2:1)$, $\Delta E^*cmc(1:1)$, ΔE^*00 , ΔE Hunter Colour Difference Formulas; and can be set to D65, A, C, D50, D55, D75, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12 illuminants. In addition, the TR 520 can report a wide selection of other Colorimetric Index's: WI (ASTM E313, CIE/ISO, AATCC, Hunter), YI (ASTM D1925, ASTM 313), TI (ASTM, E313, CIE/ISO), Metamerism Index (MI), Colour stain, Colour Fastness, Colour Strength and Opacity. This data can be seen as either Spectral Value/ Graph, Colorimetric Value, Colour Difference Value/ Graph, PASS/FAIL Result, Colour Offset or Samples Chromaticity values

Sanayi

Diğer Sanayiler | İlaç Sanayi | Kimya Sanayi | Yağ ve Gaz | Yiyecek-ve İçecek Sanayi

Uygulama

Ev Ürünleri | Kaplamalar | Plastikler | Tekstiller

TR 520 Spectrophotometer

The Lovibond TR Series of spectrophotometers and reflectance meters allow you to measure a variety of unique surfaces. Offering a consistent and accurate colour measurement, the TR series will reduce rejection rate and help improve your production speed. The ergonomic design and flexibility of the devices make them perfect for a variety of different industries including paints, coatings, plastics, textiles, printing, food, cosmetics and creams. Select from our product range below and find your colour measurement solution within the Lovibond TR Series.

Teknik Veri

Applicable Standard	ASTM 313 ASTM D1925 ASTM E308
Renk Türü	Opaque
Optik Geometri	Reflect: di: 8°, de: 8° (diffused illumination, 8 degree viewing angle)
Entegre Edilebilir Küre Boyutu	48 mm
Spektrofotometrik Mod	Concave Grating
Sensor	256 image Element Double Array CMOS Image Sensor
Ekran	3.5 inch TFT colour LCD, Capacitive Touch Screen
Arayüzler	USB
Spektral Periyod	10 nm
Ölçüm Modu	Single Measurement, Average Measurement
Harici Depolama	2000 Standards : 20000 Samples
Konum Metodu	Camera View Finder Locating
Ölçülen Reflektans Aralığı	0 - 200 %
Ölçüm Süresi	2.6 s
Diyafram Ölçümü	Dual Aperture: 10mm/8mm & 5mm/4mm
Yansıtıcıya Ait Bileşen	SCI & SCE
Renk Farkı Formülü	ΔE^*ab , ΔE^*uv , ΔE^*94 , ΔE^*cmc (2:1), ΔE^*cmc (1:1), ΔE^*00v , ΔE (Hunter)
Pil Ömrü	5000 measurements with 8 hours
Diğer Kolorimetrik Endeks	WI (ASTM E313, CIE/ISO, AATCC, Hunter) YI (ASTM D1925, ASTM 313, TI (ASTM E313, CIE/ISO) Metamerism Index MI, Staining Fastness, Colour Fastness, Colour Strength, Opacity
Gösterilen Veri	Spectrogram/Values, Samples Chromaticity Values, Colour Difference Values/Graph, PASS/FAIL Result, Colour Offset
Enstrümanlar Arası Uyum	MAV/SCI: $\Delta E^* \leq 0.15$
Spektral Aralık	400 - 700 nm
Bant Genişliği	10 nm

İllüminantlar	CIE Illuminant D65 CIE Illuminant A CIE Illuminant C CIE Illuminant D50 CIE Illuminant D55 CIE Illuminant D75 CIE Illuminant F1 CIE Illuminant F2 CIE Illuminant F3 CIE Illuminant F4 CIE Illuminant F5 CIE Illuminant F6 CIE Illuminant F7 CIE Illuminant F8 CIE Illuminant F9
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CIE Illuminant F10
CIE Illuminant F11
CIE Illuminant F12

Taşınabilirlik	Taşınabilir
Aydınlatıcı Ömrü	5 years, more than 3 million measurements
Gözlemci	2° / 10°
Diller Kullanıcı Arabirimi	İngilizce, Almanca, Fransızca, İspanyolca, Portekizce, Çince
Boyutlar	184 x 105 x 77 mm

Teslimat Kapsam Metni

- TR 520 Sphere Spectrophotometer
- OnShade PC Software
- White and Black Calibration Board
- Dust Cover
- USB Cable
- External DC Power Supply
- USB Stick with User Manuals in English, French, German, Spanish, Portuguese and Chinese
- Sturdy Carrying Case

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Almanya

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
Birleşik Krallık

Tintometer China

9F, SOHO II C. No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care Tel.: +86 (021) 69910081
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
Çin

Lovibond Tintometer Sdn Bhd

Unit B-3-12, BBT One Boulevard,
Lebuh Batu Nilam 2, Bdr Bkt Tinggi,
41200, Klang, Selangor,
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malezya

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brezilya

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Amerika Birleşik Devletleri

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
Hindistan

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
İspanya